# **Environmental Product Declaration (EPD)**



Note: This EPD was made based on a LCA-tool.







ift

**ROSENHEIM** 

SIEGENIA-AUBI KG

# **Drive systems**

# **Electric drives for windows**





DIN EN ISO 14025 EN 15804 + A2

Company EPD Environmental Product Declaration

> Publication date: 19.09.2023 Valid until:

19.09.2028



ift Rosenheim GmbH Theodor-Gietl-Str. 7-9 D-83026 Rosenheim Kontakt Tel.: +49 8031 261-0 Fax: +49 8031 261-290 www.ift-rosenheim.de Prüfung und Kalibrierung – EN ISO/IEC 17025 Inspektion – EN ISO/IEC 17020 Zertifizierung Produkte – EN ISO/IEC 17065 Zertifizierung Managementsysteme – EN ISO/IEC 17021

Notified Body 0757



# **Environmental Product Declaration (EPD)**

# Declaration code: EPD-SIZ-GB-75.0.01

Programme operator	ift Rosenheim GmbH Theodor-Gietl-Straße 7-9 D-83026 Rosenheim								
Tool creator / LCA practitioner	Sphera Solutions GmbH Hauptstraße 111-113 70771 Leinfelden-Echterdingen								
Tool-Inhaber / Declaration holder	SIEGENIA-AUBI KG Industrierstraße 1-3 D-57234 Wilnsdorf www.siegenia.com								
Declaration code	EPD-SIZ-GB-75.0.01								
Designation of declared product	Electric drives for windows								
Scope	Concealed tilt drive for mod	dern fanlights for windows							
Basis	This EPD was prepared on the basis of EN ISO 14025:2011 and DIN EN 15804:2012+A2:2019. In addition, the "Allgemeiner Leitfaden zur Erstellung von Typ III Umweltproduktdeklarationen" (Guidance on preparing Type III Environmental Product Declarations) applies. The Declaration is based on the PCR documents "PCR Part A" PCR-A-0.2:2018 and "Drive systems" PCR-AFT-								
	Publication date: 19.09.2023	Last revision: 19.09.2023	Valid until: 19.09.2028						
Validity	This verified company Environmental Product Declaration applies solely to the specified products and is valid for a period of five years from the date of publication in accordance with DIN EN 15804.								
LCA basis	The LCA was prepared in accordance with DIN EN ISO 14040 and DIN EN ISO 14044. The base data includes both the data collected at the SIEGENIA-AUBI KG and the generic data from the "Sphera - LCA for Expert Content version 2023.1". The calculations were made by the LCA-Tool Sphera - LCA for Expert Content version 2023.1. The LCA calculations were carried out for the cradle to gate with options life cycle including all upstream chains (e.g. raw material extraction, etc.)								
Notes	The "Conditions and Guidance on the Use of ift Test Documents" apply. The declaration holder assumes full liability for the underlying data, certificates and verifications.								
Christian / En	nor T. Mie	ahe Ssa	une Volz						

Christian Kehrer Head of Certification and Surveillance Body Dr. Torsten Mielecke Chairman of Expert Committee ift-EPD and PCR Susanne Volz Externernal verifier

ift Rosenheim GmbH Theodor-Gietl-Str. 7-9 D-83026 Rosenheim Kontakt Tel.: +49 8031 261-0 Fax: +49 8031 261-290 www.ift-rosenheim.de

Prüfung und Kalibrierung – EN ISO/IEC 17025 Inspektion – EN ISO/IEC 17020 Zertifizierung Produkte – EN ISO/IEC 17065 Zertifizierung Managementsysteme – EN ISO/IEC 17021

Notified Body 0757 PÜZ-Stelle: BAY 18



**ROSENHEIM** 



### **Product group: drive**

# **1** General product information

**Product definition** 

The EPD relates to the product group drive and applies to:

# 1 piece of drive made by SIEGENIA-AUBI KG

The declared unit is obtained as follows:

Assessed product	Declared unit	Unit weight						
Axxent DRIVE FPi	1 piece	0,65 kg/piece						
Table 1: Product groups								

The average unit is declared as follows:

Directly used material flows are determined using masses (kg) produced and assigned to the declared unit. All other inputs and outputs in the production are assigned to the declared unit in their entirety because they cannot be related to the average size. The reference period is the year 2022.

The validity of the EPD is restricted to the following models:

- DRIVE FPi
- DRIVE CL

-

DRIVE axxent DK

**Product description** Concealed automatic tilt locking drive for tilt and tilt turn windows and door fittings. Control possible via button switch, radio remote or with a smartphone/tablet and the SIEGENIA app (smart version). Can be integrated into group controls or building technology (e.g. KNX). Operating voltage 24V DC. Manual, simple operation possible in the event of a power failure.

For a detailed product description refer to the manufacturer specifications or the product specifications of the respective offer/quotation.



Scope

Area of application, amongst other, for:

- effective and comfortable ventilation
- difficult to reach upper areas

**Product group: drive** 

Page 4



#### Management systems The following management systems are in place: Quality management system accordance with • in DIN EN ISO 9001:2015 Environmental management systems in accordance with • DIN EN ISO 14001:2015 Additional information For additional evidence of fitness for use or certificates of conformity, if applicable, please refer to the CE marking and the documents accompanying the product 2 Materials used **Primary materials** The primary materials used are specified in Section 6.2 Inventory analysis (Inputs). The raw materials used can be found in the life cycle assessment. **Declarable substances** The product contains substances from the REACH candidate list (declaration dated 04. may 2023). All relevant safety data sheets as well as die Konformitätserklärung RoHS-REACH are available from SIEGENIA-AUBI KG. Therefore see also https://www.siegenia.com. 3 **Construcion process stage**

# ProcessingObserve the instructions for mounting/installation, operation,<br/>maintenance and disassembly, provided by the manufacturer. See<br/>https://www.siegenia.com.

# 4 Use stage

Reference service life (RSL) The RSL information was provided by the manufacturer. The RSL shall be specified under defined reference in-use conditions and shall refer to the declared technical and functional performance of the product within the building. It shall be established in accordance with any specific rules given in European product standards, or, if not available, in accordance with a c-PCR. It shall also take into account ISO 15686-1, -2, -7 and -8. Where European product standards or a c-PCR provide guidance on deriving the RSL, such guidance shall have priority. If it is not possible to determine the service life as the RSL in accordance with ISO 15686, the BBSR table "Nutzungsdauer von Bauteilen zur Lebenszyklusanalyse nach BNB" (service life of building components for life cycle assessment in accordance with the sustainable construction evaluation system) can be used. For further information and explanations refer to www.nachhaltigesbauen.de.



### Product group: drive

For this EPD the following applies:

For a "Cradle to gate with options" EPD with the modules C1-C4 and module D (A1-A3 + C + D and one or more additional modules from A4 to B7), the reference service life (RSL) can only be stated if the reference inuse conditions are specified.

According to the manufacturer, an optional service life of 10 years is specified for electric drives for windows made by SIEGENIA-AUBI KG.

The reference service life is dependent on the characteristics of the product and the reference in-use conditions. The in-use conditions described in the EPD are applicable, in particular the characteristics listed below:

- Outdoor environment: Climatic influences may have a negative impact on the reference service life
- Indoor environment: No factors (e.g. humidity, temperature) known that may have a negative effect on the reference service life.

The service life applies solely to the characteristics specified in this EPD or the corresponding references.

The RSL does not reflect the actual life span, which is usually determined by the service life and the refurbishment of a building. It does not give any information on the useful life, warranty referring to performance characteristics or guarantees.

# 5 End-of-life stage

**Possible end-of-life stages** The electric drives for windows are shipped to central collection points. There the products are generally shredded and sorted into their original constituents. The end-of-life stage depends on the site where the products are used and is therefore subject to the local regulations. Observe the locally applicable regulatory requirements.

This EPD shows the end-of-life modules according to the market situation. Specific components of steel and plastics are recycled. Residual fractions are sent to landfill or partially thermally recycled.

**Disposal routes** The LCA includes the average disposal routes.

All life cycle scenarios are detailed in the Annex.



### **Product group: drive**

# 6 Life Cycle Assessment (LCA)

Environmental product declarations are based on life cycle assessments (LCAs) which use material and energy flows for the calculation and subsequent representation of environmental impacts

Such a life cycle assessment was developed for electric drive for windows, serving as the basis. The LCA is in conformity with the requirements set out in DIN EN 15804 and the international standards DIN EN ISO 14040, DIN EN ISO 14044 and EN ISO 14025 as well as based on ISO 21930.

The LCA is representative of the products presented in the Declaration and the specified reference period.

### 6.1 Definition of goal and scope

Goal

The goal of the LCA is to demonstrate the environmental impacts of the products. In accordance with DIN EN 15804, the environmental impacts covered by this Environmental Product Declaration are presented for the entire product life cycle in the form of basic information. Apart from these, no other environmental impacts are specified.

Data quality, data<br/>availability and<br/>geographical and time-<br/>related system boundariesThe specific data originate exclusively from the 2022 fiscal year. They<br/>were collected on-site at the plant located in DE-57234 Wilnsdorf and in<br/>PL-46-203 Kluczbork and come in parts from company records and partly<br/>from values directly obtained by measurement. Validity of the data was<br/>checked by the tool creator /LCA practitioner.

The generic data come from the "Sphera - LCA for Expert Content version 2023.1" professional and building materials databases. The last update of both databases was in 2023. Data from before this date come also from these databases and are not more than five years old. No other generic data were used for the calculation.

The generic data selected are as accurate as possible in terms of geographical reference. If no country-specific datasets are available or regional reference cannot be established, European or global datasets are used.

Data gaps were either filled with comparable data or conservative assumptions, or the data were cut off in compliance with the 1% rule.

The life cycle was modelled using the sustainability software tool "Sphera - LCA for Experts; Content version 2023.1".

**Scope/ system boundaries** The system boundaries refer to the supply of raw materials and purchased parts, manufacture, use and end-of-life stage of electric drives for windows.

No additional data from pre-suppliers or other sites were taken into consideration.

# Product group: drive

Page 7



Cutt-off criteria	All the data that the company records, i.e. all commodities/input and raw materials used, the thermal energy used and electricity consumption, were taken into consideration.
	<ul> <li>The following data were cut off:</li> <li>Packaging production of preliminary products</li> <li>Packaging transportation of final product</li> <li>Auxiliary and operating materials</li> </ul>
	The boundaries cover only the product-relevant data. Building sections/parts of facilities that are not relevant to the manufacture of the products, were excluded.
	The transport distances of the pre-products were taken into consideration as a function of 100% of the mass of the products.
	The criteria for the exclusion of inputs and outputs as set out in DIN EN 15804 are fulfilled. From the data analysis it can be assumed that the total of negligible processes per life cycle stage does not exceed 1% of the mass/primary energy. All in all, the total of negligible processes does not exceed 5% of the energy and mass input. The life cycle calculation also includes material and energy flows that account for less than 1%.
6.2 Inventory analysis	
Goal	All material and energy flows are described below. The processes covered are presented as input and output parameters and refer to the declared unit.
Life cylce stages	The Annex shows the entire life cycle of electric drives for windows. The "Product Stage" (A1 – A3), "Construction process stage" (A4 – A5), "Use stage" (B2 and B6), "End-of-life" (C1 – C4) and the "Benefits and loads beyond the system boundaries" (D) are considered.
Benefits	<ul> <li>The below benefits have been defined in accordance with DIN EN 15804:</li> <li>Benefits from recycling</li> <li>Benefits (thermal and electrical) from incineration</li> </ul>
Allocation of co-products	No allocation occur during manufacturing.
Allocations for reuse, recycling and recovery	If the products are reused/recycled and recovered during the product stage (rejects) the components are shredded if necessary and then sorted into their single constituents. This is done by various process plants, e.g. magnetic separators.
Allocations beyond life cycle boundaries	The system boundaries were set following their disposal, reaching the end-of-waste state. The use of recycled materials in the manufacturing process was based on the current market-specific situation. A recycling potential that reflects the economic value of the product after recycling (recyclate) was also taken into account .

EPD Electric drives for windows Declaration code: EPD-SIZ-GB-75.0.01

Publication date: 19.09.2023

**Product group: drive** 



	Secondary material stated as input into the production of electric drives for windows, is calculated in module A1 without loads. No benefits are allocated to module D, but consumption is allocated to module/modules C3 and C4 (worst case scenario). The system boundary set for the recycled material refers to collection.
Secondary Materials	<ul> <li>The use of secondary material by SIEGENIA-AUBI KG was considered in module A3. Secondary material was used:</li> <li>Metal scrap in steel, stainless steel and aluminum production</li> <li>Waste paper in the production of packaging boxes</li> </ul>
Inputs	The LCA includes the following producion-relevant inputs per 1 piece of drive:
	<b>Energy</b> The gas input material is based on "Erdgas Deutschland" (natural gas Germany) and "Erdgas Polen" (natural gas Poland). Diesel is based on "Diesel Europa". The electricity mix is based on "Strommix Deutschland" (electricity mix Germany) and "Strommix "Polen" (electricity mix Poland). The light heating oil input material is based on "leichtes Heizöl Deutschland" (light heating oil Germany) and the biogas input is based on "Biogas Deutschland" (biogas Germany).
	A portion of the process heat is used for space heating. This can, however, not be quantified and a "worst case" figure was taken into account for the product.
	Water No water is consumed by the individual process steps for the production. The consumption of freshwater specified in Section 6.3 originates (among others) from the process chain of the pre-products

### Raw material/pre-products

The chart below shows the share of raw materials/pre-products in %.



Figure 1: Percentage of individual materials per declared unit

Page 9



### Product group: drive

No.	Material	Mass in %
1	Zinc	50 %
2	Steel	26 %
3	Engine	18 %
4	Stainless steel	5 %
5	Plastic	3 %

**Table 2**: Percentage of individual materials per declared unit

### Ancillary materials and consumables

Ancillary materials and consumables are cut off.

### **Product packaging**

The amounts used for product packaging are as follows:

No.	Material	Mass in g
1	Wood	0,49
2	Cardboard	62,50
3	PE-film	4,13

**Table 3:** Weight in g of packaging per declared unit

### **Biogenic carbon content**

Only the biogenic carbon content of the associated packaging is specified, as the total mass of substances containing biogenic carbon is less than 5% of the total mass of the product and associated packaging. In accordance with EN 16449, packaging produces the following amounts of biogenic carbon:

No.	Component	Content in kg C per piece					
1	Associated packaging	2,71E-02					
Table 0. Discussion and an accustoriated the sum durated at mate							

 Table 2: Biogenic carbon content of the product at gate

The LCA includes the following production-relevant outputs per 1 piece of drive:

### Waste

Secondary raw materials were included in the benefits. See Section 6.3 Impact assessment.

### Waste water

The manufacture does not produce any waste water.

### 6.3 Impact assessment

Goal

Outputs

The impact assessment covers both inputs and outputs. The impact categories applied are named below:

# **Product group: drive**

Core indicators

The models for impact assessment were applied as described in DIN EN 15804+A2.

The impact categories presented in the EPD as core indicators are as follows:

- Climate change total (GWP-t) •
- Climate change fossil (GWP-f) •
- Climate change – biogenic (GWP-b)
- Climate change land use and land use change (GWP-I) •
- Ozone depletion (ODP) •
- Acidification (AP) •
- Eutrophication aquatic freshwater (EP-fw) •
- Eutrophication aquatic marine (EP-m) •
- Eutrophication terrestrial (EP-t) •
- Photochemical ozone creation (POCP) •
- Depletion of abiotic resources fossil fuels (ADPF)
- Depletion of abiotic resources minerals and metals (ADPE)
- Water use (WDP)



### Use of resources

The models for impact assessment were applied as described in DIN EN 15804-A2.

The following parameters for the use of resources are shown in the EPD:

- Renewable primary energy as energy source (PERE) •
- Renewable primary energy for material use (PERM) •
- Total use of renewable primary energy (PERT) •
- Non-renewable primary energy as energy resource (PENRE) •
- Renewable primary energy for material use (PENRM) •
- Total use of non-renewable primary energy (PENRT) •
- Use of secondary materials (SM) •
- Use of renewable secondary fuels (RSF) •
- Use of non-renewable secondary fuels (NRSF)
- Net use of freshwater resources (FW) •

PFRF









PENRM



ROSENHEIM





PENRE



### Product group: drive

Page 11



### Waste

The waste generate during the production of 1 piece of drive is evaluated and shown separately for the fractions trade wastes, special wastes and radioactive wastes. Since waste handling is modelled within the system boundaries, the amounts shown refer to the deposited wastes. A portion of the waste indicated is generated during the manufacture of the preproducts.

The models for impact assessment were applied as described in DIN EN 15804-A2.

The waste categories and indicators for output material flows presented in the EPD are as follows:

- Hazardous waste disposed (HWD)
- Non-hazardous waste disposed (NHWD)
- Radioactive waste disposed (RWD)
- Components for reuse (CRU)
- Materials for recycling (MFR)
- Materials for energy recovery (MER)
- Exported electrical energy (EEE)
- Exported thermal energy (EET)



# Additional environmental impact indicators

The models for impact assessment were applied as described in DIN EN 15804-A2.

The additional impact categories presented in the EPD are as follows:

- Particulate matter emissions (PM)
- Ionising radiation, human health (IRP)
- Ecotoxicity freshwater (ETP-fw)
- Human toxicity cancer effect (HTP-c)
- Human toxicity non-cancer effect (HTP-nc)
- Land use related impacts / soil quality (SQP)



:6	10															
ITC	Unit	A1 A2	A.4	<b>^</b> 5	D1					D6	D7	C1	<u>C2</u>	02	C1	<b>D</b>
ROSENHEIM	Offic		A4		ы		Core indic	ators	65		57		62	0.5	64	U
GWP-t	ka CO₂ ea.	2.87	5.76E-03	0.11	ND	0.00	ND	ND	ND	0.79	ND	1.29E-03	2.61E-03	4.88E-02	4.52E-06	-1.71
GWP-f	ka CO <sub>2</sub> ea.	2,95	5,71E-03	1,45E-02	ND	0,00	ND	ND	ND	0,79	ND	1,29E-03	2,59E-03	4,88E-02	4,51E-06	-1,70
GWP-b	kg CO <sub>2</sub> eg.	-8,85E-02	5,96E-07	9,88E-02	ND	0,00	ND	ND	ND	3,93E-04	ND	6,44E-07	2,70E-07	4,40E-06	5,89E-14	-2,27E-03
GWP-I	kg CO <sub>2</sub> eq.	2,18E-03	5,28E-05	2,61E-06	ND	0,00	ND	ND	ND	7,23E-05	ND	1,18E-07	2,39E-05	3,89E-07	1,40E-08	-9,20E-04
ODP	kg CFC-11 eq.	7,61E-12	7,42E-16	1,34E-14	ND	0,00	ND	ND	ND	7,77E-12	ND	1,27E-14	3,36E-16	7,28E-15	1,15E-17	-4,08E-12
AP	mol H⁺ eq.	1,38E-02	8,34E-06	3,75E-06	ND	0,00	ND	ND	ND	1,20E-03	ND	1,97E-06	3,78E-06	3,12E-05	3,20E-08	-8,22E-03
EP-fw	kg P eq.	5,81E-06	2,08E-08	2,42E-09	ND	0,00	ND	ND	ND	7,81E-07	ND	1,28E-09	9,45E-09	2,09E-09	9,08E-12	-3,56E-06
EP-m	kg N eq.	2,51E-03	3,02E-06	9,96E-07	ND	0,00	ND	ND	ND	3,39E-04	ND	5,56E-07	1,37E-06	1,50E-05	8,26E-09	-1,15E-03
EP-t	mol N eq.	2,70E-02	3,57E-05	1,40E-05	ND	0,00	ND	ND	ND	3,59E-03	ND	5,87E-06	1,62E-05	1,73E-04	9,09E-08	-1,23E-02
POCP	kg NMVOC eq.	7,75E-03	7,30E-06	2,76E-06	ND	0,00	ND	ND	ND	9,38E-04	ND	1,54E-06	3,31E-06	3,85E-05	2,49E-08	-4,02E-03
ADPF*2	MJ	5,09E-04	3,75E-10	8,66E-11	ND	0,00	ND	ND	ND	3,83E-08	ND	6,27E-11	1,70E-10	6,38E-11	2,08E-13	-5,24E-04
ADPE*2	kg Sb eq.	35,92	7,77E-02	3,38E-02	ND	0,00	ND	ND	ND	17,40	ND	2,84E-02	3,52E-02	1,74E-02	6,00E-05	-19,50
WDP*2	m <sup>3</sup> world eq. deprived	0,59	6,89E-05	1,38E-03	ND	0,00	ND	ND	ND	6,64E-02	ND	1,09E-04	3,12E-05	5,86E-03	4,95E-07	-0,33
						ι	Jse o resc	ources								
PERE	MJ	11,64	5,65E-03	1,14	ND	0,00	ND	ND	ND	2,38	ND	3,89E-03	2,56E-03	4,03E-03	9,78E-06	-4,21
PERM	MJ	0,00	0,00	-1,13	ND	0,00	ND	ND	ND	0,00	ND	0,00	0,00	0,00	0,00	0,00
PERT	MJ	11,64	5,65E-03	4,59E-03	ND	0,00	ND	ND	ND	2,38	ND	3,89E-03	2,56E-03	4,03E-03	9,78E-06	-4,21
PENRE	MJ	36,02	7,80E-02	0,22	ND	0,00	ND	ND	ND	17,40	ND	2,84E-02	3,53E-02	0,57	6,01E-05	-19,60
PENRM	MJ	0,00	0,00	-0,19	ND	0,00	ND	ND	ND	0,00	ND	0,00	0,00	-0,55	0,00	0,00
PENRT	MJ	36,02	7,80E-02	3,38E-02	ND	0,00	ND	ND	ND	17,40	ND	2,84E-02	3,53E-02	1,74E-02	6,01E-05	-19,60
SM	kg	7,95E-02	0,00	0,00	ND	0,00	ND	ND	ND	0,00	ND	0,00	0,00	0,00	0,00	0,60
RSF	MJ	0,00	0,00	0,00	ND	0,00	ND	ND	ND	0,00	ND	0,00	0,00	0,00	0,00	0,00
NRSF	MJ	0,00	0,00	0,00	ND	0,00	ND	ND	ND	0,00	ND	0,00	0,00	0,00	0,00	0,00
FW	m³	2,14E-02	6,19E-06	3,65E-05	ND	0,00	ND	ND	ND	3,98E-03	ND	6,52E-06	2,81E-06	1,38E-04	1,52E-08	-9,97E-03
						v	laste cate	gories		<u>,                                     </u>						
HWD	kg	5,98E-06	2,41E-13	1,70E-12	ND	0,00	ND	ND	ND	1,01E-09	ND	1,65E-12	1,09E-13	1,04E-12	1,31E-15	7,10E-10
NHWD	kg	0,80	1,19E-05	7,13E-05	ND	0,00	ND	ND	ND	3,83E-03	ND	6,27E-06	5,39E-06	2,03E-03	3,00E-04	-3,73E-02
RWD	kg	1,67E-03	1,46E-07	4,54E-06	ND	0,00	ND	ND	ND	2,71E-03	ND	4,43E-06	6,61E-08	6,55E-07	6,85E-10	-8,19E-04
						Out	put mater	rial flows								
CRU	kg	0,00	0,00	0,00	ND	0,00	ND	ND	ND	0,00	ND	0,00	0,00	0,00	0,00	0,00
MFR	kg	0,00	0,00	0,00	ND	0,00	ND	ND	ND	0,00	ND	0,00	0,00	0,00	0,00	0,00
MER	kg	0,00	0,00	0,00	ND	0,00	ND	ND	ND	0,00	ND	0,00	0,00	0,00	0,00	0,00
EEE	MJ	0,00	0,00	2,85E-02	ND	0,00	ND	ND	ND	0,00	ND	0,00	0,00	0,00	0,00	0,00
EET	MJ	0,00	0,00	5,07E-02	ND	0,00	ND	ND	ND	0,00	ND	0,00	0,00	0,00	0,00	0,00
Key: GWP-t – gl use change feutrophica minerals&n	Key: GWP-t – global warming potential - total GWP-f – global warming potential fossil fuels GWP-b – global warming potential - biogenic GWP-I – global warming potential - land use and land use change ODP – ozone depletion potential AP - acidification potential EP-fw - eutrophication potential - aquatic freshwater EP-m - eutrophication potential - aquatic marine EP-t - feutrophication potential - terrestrial POCP - photochemical ozone formation potential ADPF <sup>*2</sup> - abiotic depletion potential – fossil resources ADPE <sup>*2</sup> - abiotic depletion potential – minerals&metals WDP <sup>*2</sup> – Water (user) deprivation potential PERE - Use of renewable primary energy PERM - use of renewable primary energy resources PERT - total use of															

renewable primary energy resources **PENRE** - use of non-renewable primary energy **PENRM** - use of non-renewable primary energy resources **PENRT** - total use of non-renewable primary energy resources **SM** - use of secondary material **RSF** - use of renewable secondary fuels **NRSF** - use of non-renewable secondary fuels **FW** - net use of fresh water **HWD** - hazardous waste disposed **NHWD** - non-hazardous waste disposed **RWD** - radioactive waste disposed **CRU** - components for re-use **MFR** - materials for recycling **MER** - materials for recycling **MER** - materials for energy recovery **EEE** - exported electrical energy **EET** - exported thermal energy

ift	Results per 1 piece of axxent drive															
ROSENHEIM	Einheit	A1-A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
					Add	itional env	vironmenta	l impact i	ndicators							
РМ	Disease incidence	1,65E-07	7,18E-11	2,94E-11	ND	0,00	ND	ND	ND	1,09E-08	ND	1,78E-11	3,25E-11	1,25E-10	3,93E-13	-1,00E-07
IRP*1	kBq U235 eq.	0,20	2,18E-05	6,82E-04	ND	0,00	ND	ND	ND	0,41	ND	6,65E-04	9,86E-06	9,34E-05	7,91E-08	-0,10
ETP-fw <sup>*2</sup>	CTUe	10,71	5,52E-02	1,15E-02	ND	0,00	ND	ND	ND	4,97	ND	8,14E-03	2,50E-02	7,05E-03	3,27E-05	-8,83
HTP-c*2	CTUh	6,00E-08	1,13E-12	2,91E-13	ND	0,00	ND	ND	ND	8,97E-11	ND	1,47E-13	5,12E-13	4,45E-13	5,04E-15	3,52E-09
HTP-nc* <sup>2</sup>	CTUh	1,89E-07	6,02E-11	1,33E-11	ND	0,00	ND	ND	ND	4,59E-09	ND	7,52E-12	2,73E-11	4,18E-11	5,54E-13	5,04E-07
SQP*2	Dimensionless	14,99	3,25E-02	5,90E-03	ND	0,00	ND	ND	ND	2,35	ND	3,85E-03	1,47E-02	4,17E-03	1,46E-05	-1,74
Surr       Dimensionless       ND       3,85E-03       1,47E-03       1,40E-03       -1,74         Key:       PM – particulate matter emissions potential       IRP*1 – ionizing radiation potential – human health       ETP-fw*2 - Eco-toxicity potential – freshwater       HTP-c*2 - Human toxicity potential – cancer         effects       HTP-nc*2 - Human toxicity potential – non-cancer effects       SQP*2 – soil quality potential																

Disclaimers \*1 This impact category deals mainly with the eventual impact of low-dose ionising radiation on human health of the nuclear fuel cycle. It does not consider effects due to possible nuclear accidents, occupational exposure nor due to radioactive waste disposal in underground facilities. Potential ionising radiation from the soil, from radon and from some building materials is also not measured by this indicator

\*2 The results of this environmental impact indicator shall be used with care as the uncertainties on these results are high or as there is limited experience with the indicator

### Page 14



### **Product group: Drive**

### 6.4 Interpretation, LCA presentation and critical review

Auswertung It is recognizable that the manufacturing phase is dominant in the product stage. (module A1-A3). The use phase (module B6) contributes second strongest to the GWPimpacts due to the daily electricity use. The end-of-life phase has little impact due to the high proportion of recycable materials. The recycling of metal parts and the avoided burdens contribute considerably to the credits in module D. The modules A4, A5, C1 and C2 also contribute with low impacts.

The following figure shows the results of the individual modules as an example of the global warming potential:



Figure 2: Percentage of the modules in selected environmental impact categories

# The values obtained from the LCA calculation are suitable for the certification of buildings.

- **Report** The LCA report underlying this EPD was developed according to the requirements of DIN EN ISO 14040 and DIN EN ISO 14044 as well as DIN EN 15804 and DIN EN ISO 14025. It is not addressed to third parties for reasons of confidentiality. It is deposited with the ift Rosenheim. The results and conclusions reported to the target group are complete, correct, without bias and transparent. The results of the study are not designed to be used for comparative statements intended for publication.
- **Critical Review** The critical review of the LCA was carried out by Dipl. Wirtschaftsjuristin (FH) Susanne Volz, M Sc. Environmental Sciences, an independent ift verifier.

# 7 General information regarding the EPD

- Comparability This EPD was prepared in accordance with DIN EN 15804 and is therefore only comparable to those EPDs that also comply with the requirements set out in DIN EN 15804.
   Any comparison must refer to the building context and the same boundary conditions of the various life cycle stages.
   For comparing EPDs of construction products, the rules set out in DIN EN 15804 (Clause 5.3) apply.
- **Communication** The communications format of this EPD meets the requirements of EN 15942:2012 and is therefore the basis for B2B communication. Only the nomenclature has been changed according to DIN EN 15804.

Page 15



### **Product group: Drive**

**Verification** Verification of the Environmental Product Declaration is documented in accordance with the ift "Richtlinie zur Erstellung von Typ III Umweltproduktdeklarationen" (Guidance on preparing Type III Environmental Product Declarations) in accordance with the requirements set out in DIN EN ISO 14025

The Declaration is based on the PCR documents "PCR Teil A" PCR-A-0.2.2018 and "Antriebe" (drives) PCR-AFT-3.0:2021

The European standard EN 15804 serves as the core PCR <sup>a)</sup>
Independent external verification of the Declaration and statement
according to EN ISO 14025:2010
Independent third party verifier: b)
Susanne Volz
<sup>a)</sup> Product category rules
<sup>b)</sup> Optional for business-to-business communication
Mandatory for business-to-consumer communication
(see EN ISO 14025:2010, 9.4)

# Revisions of this document

his	No.	Date	Note	Practitioner	Verifier
	1	19.09.2023	External verification	Seehauser / Dellawalle	Volz

Publication date: 19.09.2023

#### **Product group: Drive**

### 8 Literaturverzeichnis

1. **PCR Teil A.** Allgemeine Produktkategorieregeln für Umweltprodukdeklarationen nach EN ISO 14025 und EN 15804. Rosenheim : ift Rosenheim, 2018.

2. **ift-Richtlinie NA-01/3.** *Allgemeiner Leitfaden zur Erstellung von Typ III Umweltproduktdeklarationen.* Rosenheim : ift Rosenheim GmbH, 2015.

3. Klöpffer, W und Grahl, B. Ökobilanzen (LCA). Weinheim : Wiley-VCH-Verlag, 2009.

4. Eyerer, P. und Reinhardt, H.-W. Ökologische Bilanzierung von Baustoffen und Gebäuden - Wege zu einer ganzheitlichen Bilanzierung. Basel : Birkhäuser Verlag, 2000.

5. **Gefahrstoffverordnung - GefStoffV.** Verordnung zum Schutz vor Gefahrstoffen. Berlin : BGBI. I S. 3758, 2017.

6. **Chemikalien-Verbotsverordnung - ChemVerbotsV.** Verordnung über Verbote und Beschränkungen des Inverkehrbringens gefährlicher Stoffe, Zubereitungen und Erzeugnisse nach Chemikaliengesetz. Berlin : BGBI. I S. 1328, 2017.

7. **DIN EN ISO 14040:2018-05.** Umweltmanagement - Ökobilanz - Grundsätze und Rahmenbedingungen. Berlin : Beuth Verlag GmbH, 2018.

8. **DIN EN ISO 14044:2006-10.** Umweltmanagement - Ökobilanz - Anforderungen und Anleitungen. Berlin : Beuth Verlag GmbH, 2006.

9. EN ISO 14025:2011-10. Umweltkennzeichnungen und deklarationen Typ III Umweltdecklarationen - Grundsätze und Verfahren. Berlin : Beuth Verlag GmbH, 2011.

10. **OENORM S 5200:2009-04-01.** Radioaktivität in Baumaterialien. Berlin : Beuth Verlag GmbH, 2009.

11. EN 15942:2012-01. Nachhaltigkeit von Bauwerken -Umweltproduktdeklarationen - Kommunikationsformate zwischen Unternehmen. Berlin : Beuth Verlag GmbH, 2012.

12. Bundesministerium für Umwelt, Naturschutz, Bau und Reaktorsicherheit. *Leitfaden Nachhaltiges Bauen.* Berlin : s.n., 2016.

13. **DIN EN 13501-1:2010-01.** Klassifizierung von Bauprodukten und Bauarten zu ihrem Brandverhalten - Teil 1: Klassifizierung mit den Ergebnissen aus den Prüfungen zum Brandverhalten von Bauprodukten. Berlin : Beuth Verlag GmbH, 2010.

14. **DIN ISO 16000-6:2012-11.** Innenraumluftverunreinigungen - Teil 6: Bestimmung von VOC in der Innenraumluft und in Prüfkammern, Probenahme auf TENAX TA®, thermische Desorption und Gaschromatografie mit MS/FID. Berlin : Beuth Verlag GmbH, 2012.

15. **ISO 21930:2017-07.** *Hochbau - Nachhaltiges Bauen - Umweltproduktdeklarationen von Bauprodukten.* Berlin : Beuth Verlag, 2017.

16. Bundesimmissionsschutzgesetz - BlmSchG. Gesetz zum Schutz vor schädlichen Umwelteinwirkungen durch Luftverunreinigungen, Geräusche, Erschütterungen und ähnlichen Vorgängen. Berlin : BGBI. I S. 3830, 2017.

17. **Chemikaliengesetz - ChemG.** Gesetz zum Schutz vor gefährlichen Stoffen - Unterteilt sich in Chemikaliensetz und eine Reihe von Verordnungen; hier relevant: Gesetz zum Schutz vor gefährlichen Stoffen. Berlin : BGBI. I S. 1146, 2017.

Page 16



18. **IKP Universität Stuttgart und PE Europe GmbH.** *GaBi* 8: Software und Datenbank zur Ganzheitlichen Bilanzierung. Leinfelden-Echterdingen : s.n., 2017.

19. **Forschungsvorhaben.** *EPDs für transparente Bauelemente - Abschlussbericht.* Rosenheim : ift Rosenheim GmbH, 2011. SF-10.08.18.7-09.21/II 3-F20-09-1-067.

20. **DIN EN ISO 12457- Teil 1-4 :2003-01.** *Charakterisierung* von Abfällen - Auslaugung; Übereinstimmungsuntersuchung für die Auslaugung von körnigen Abfällen und Schlämmen - Teil 1-4. Berlin : Beuth Verlag GmbH, 2003.

21. **DIN EN ISO 16000-9:2008-04.** Innenraumluftverunreinigungen - Teil 9: Bestimmung der Emissionen von flüchtigen organischen Verbindungen aus Bauprodukten und Einrichtungsgegenständen -Emissionsprüfkammer-Verfahren. Berlin : Beuth Verlag GmbH, 2008.

22. **DIN EN ISO 16000-11:2006-06.** Innenraumluftverunreinigungen - Teil 11: Bestimmung der Emissionen von flüchtigen organischen Verbindungen aus Bauprodukten und Einrichtungsgegenständen - Probenahme, Lagerung der Proben und Vorbereitung der Prüfstücke. Berlin : Beuth Verlag GmbH, 2006.

23. **DIN EN 12457- Teil 1-4 :2003-01.** Charakterisierung von Abfällen - Auslaugung; Übereinstimmungsuntersuchung für die Auslaugung von körnigen Abfällen und Schlämmen - Teil 1-4. Berlin : Beuth Verlag GmbH, 2003.

24. **EN ISO 16000-11:2006-06.** Innenraumluftverunreinigungen - Teil 11: Bestimmung der Emissionen von flüchtigen organischen Verbindungen aus Bauprodukten und Einrichtungsgegenständen - Probenahme, Lagerung der Proben und Vorbereitung der Prüfstücke. Berlin : Beuth Verlag GmbH, 2006.

25. **EN ISO 16000-9:2006-08.** Innenraumluftverunreinigungen - Teil 9: Bestimmung der Emissionen von flüchtigen organischen Verbindungen aus Bauprodukten und Einrichtungsgegenständen - Emissionsprüfkammer-Verfahren. Berlin : Beuth Verlag GmbH, 2006.

26. **Umweltbundesamt.** *TEXTE* 151/2021 - Förderung einer hochwertigen Verwertung von Kunststoffabfällen aus Abbruchabfällen sowie der Stärkung des Rezyklateinsatzes in Bauprodukten im Sinne der europäischen Kunststoffstrategie. Dessau-Roßlau : Umweltbundesamt, 2021. Bde. ISSN 1862-4804.

27. **ift Rosenheim GmbH.** *Bedingungen und Hinweise zur Verwendung von ift-Prüfdokumentationen.* Rosenheim : s.n., 2016.

28. **PCR Teil B - Schlösser und Beschläge.** *Produktkategorieregeln für Umweltprodukdeklarationen nach EN ISO 14025 und EN 15804.* Rosenheim : ift Rosenheim, 2018.

29. **Sphera Solutions GmbH.** GaBi life cycle inventory data documentation. [Online] 2023. https://www.gabi-software.com/support/gabi/gabi-database-2019-lci-documentation/.

30. **SIEGENIA-AUBI KG.** Produktinformationen, RoHS, REACH-Konformitätserklärung. [Online] https://www.siegenia.com.

31. **DIN EN 15804:2012+A2:2019+AC:2021.** Nachhaltigkeit von Bauwerken - Umweltproduktdeklarationen - Grundregeln für die Produktkategorie Bauprodukte. Berlin : Beuth Verlag GmbH, 2022.

Page 17



### **Product group: Drive**

### 9 Annex

### Description of life cycle scenarios for product designation

Pro	duct st	tage	Cons tion ce sta	struc pro- ss ige			Us	se stag	je*			end-of-life stag			Benefits and loads from beyond the system boundaries	
A1	A2	A3	A4	A5	B1	B2	В3	В4	В5	B6	B7	C1	C2	C3	C4	D
Raw material supply	Transport	Manufacture	Transport	Construction/installation process	Use	Maintenance	Repair	Replacement	Modification/refurbishment	Operational use	Operational water use	Deconstruction/demolition	Transport	Waste processing	Disposal	Reuse Recovery Recycling potential
~	✓	~	~	~	_	✓				✓		~	✓	~	✓	~

\* For the declared B modules, the calculation of the results is based on the specified RSL related to one year. **Table 5**: Overview of applied life cycle stages

Calculation of the scenarios was based on a defined RSL (see Section 4 Use stage).

The scenarios were based on information provided by the manufacturer.

<u>Note:</u> The standard scenarios selected are presented in bold type. They were also used for calculating the indicators in the summary table.

- ✓ Included in the LA
- Not included in the LCA



### **Product group: Drive**

A4 Transport to construction site									
No.	Scenario	Description							
A4	Small series direct marketing	40 t LKW (Euro 6), diesel, 24,7 t payload, 61 % capacity used, about 50 km to site and empty return							
Transpo	ort to the construction site	Transport weight [kg/pc]	Density [kg/m <sup>3</sup> ]						
PG1		0,72	1193,80						
Since only one scenario is used, the results are shown in the relevant summary table.									
A5 Con	A5 Construction/installation process								
No.	Scenario	Description							
A5	Manual with power tools	According to the manufacturer the products are installed without using additional lifting and auxiliary devices Power consumption of power tools: 0,011 MJ/ pc							

In case of deviating consumption during installation/assembly of the products which forms part of the site management, they are covered at the construction works level.

Ancillary materials, consumables, use of energy and water, use of other resources, material losses, direct emissions as well as waste materials during installation are negligible.

It is assumed that the packaging material in the module "construction / installation" is sent to waste handling. Waste is only thermally recycled or disposed of in line with the conservative approach. Films/foils / protective covers, wood and cardboard in waste incineration plants. Benefits from A5 are specified in module D. Benefits from waste incineration: electricity replaces electricity mix (EU 28); thermal energy replaces thermal energy from natural gas (EU 28). Transport to the recycling plants is not taken into account.

Since only one scenario is used, the results are shown in the relevant summary table.

### B2 Cleaning, servicing and maintenance

According to the manufacturer, no inspection, maintenance or repair is neccessary for the products under consideration. Auxiliary materials, operating materials, energy/water use, waste material, material loss and transport routes can be neglected

Since only one scenario is used, the results are shown in the relevant summary table.

Page 19



# Product group: Drive

B6 Operational energy use								
Scenari	ο	Descript	ion					
Hand-oj Normal	perated use	Total pov Standby Electricit	power consumption: 6,75 MJ / 10 a energy (incl. lby operation) ricity mix (EU 28)					
Since only one scenario is used, the results are shown in the relevant summary table.								
C1 Deconstrution, demolition								
No.	Scenario		Description					
			Drive: 100 % deconstruction					
C1	Deconstruction		The product deconstruction is done with power tools. The total power usage is 0,011 MJ.					
			Further deconstruction rates are possible, give ad- equate reasons.					
Since or	hly one scenario is used, th	ie results a	ire shown in the relevant summary table.					
In case of deviating consumption, the removal of the products forms part of the site management and is covered at the construction works level.								
C2 Tran	C2 Transport							
No.	Scenario		Description					
C2	Transport		Transport to collection point using 40 t truck (Euro 6), diesel, 24,7 t payload, 61 % capacity used, 50 km					
Since only one scenario is used, the results are shown in the relevant summary table.								
C3 Waste management								
No.	Scenario		Description					
C3	Recycling		<ul> <li>Share for recirculation of materials</li> <li>Metal: 100 % Recycling</li> <li>Plastic: 100 % thermal recycling</li> </ul>					
Average costs for separating and sorting the materials are assumed.								
As the products are placed on the European market, the disposal scenario is based on average European datasets, respectively based on German datasets when there are no european datasets.								
The 100% scenarios differ from today's average recovery shown here. The evaluation of the individual scenarios is presented in the background reports								
Since only one scenario is used, the results are shown in the relevant summary table.								

# Page 20



# Product group: Drive

C4 Disp	C4 Disposal							
No.	Scenario	Description						
C4	Disposal	Materials without heat value (except metals) and the non-recordable amounts and losses within the reuse/recycling chain (C1 and C3) are modelled as "disposed" (EU-28)						
The 100 scenaric	The 100% scenarios differ from today's average recovery shown here. The evaluation of the individual scenarios is presented in the background reports							
The cons of the dis allocated Since or	The consumption in scenario C4 results from physical pre-treatment, waste recycling and management of the disposal site. The benefits obtained here from the substitution of primary material production are allocated to module D, e.g. electricity and heat from waste incineration Since only one scenario is used, the results are shown in the relevant summary table.							
D Benef	D Benefits and loads from beyond the system boundaries							
No.	Scenario	Description						
D	Debits and credits from recycling metalRecycling potentialBenefits from waste incineration: electricity mix (EU-28); thermal electricity mix (EU-28); thermal energy from natural gas							
The values in module "D" result from both the recycling of the packaging material in module A5 and the dismantling at the end of the useful life. The 100% scenarios differ from today's average recovery shown here. The evaluation of the individual scenarios is presented in the background reports								
Since or	Since only one scenario is used, the results are shown in the relevant summary table.							

# Practitioner of the LCA

Imprint







Sphera Solutions GmbH Hauptstraße 111-113 70771 Leinfelden-Echterdingen

#### Programme operator

ift Rosenheim GmbH Theodor-Gietl-Str. 7-9 D-83026 Rosenheim Phone: +49 80 31/261-0 Telefax: +49 80 31/261 290 E-Mail: info@ift-rosenheim.de www.ift-rosenheim.de

#### **Declaration holder**

SIEGENIA-AUBI KG Industrierstraße 1-3 D-57234 Wilnsdorf

#### Notes

This EPD is mainly based on the work and findings of the Institut für Fenstertechnik e.V., Rosenheim (ift Rosenheim) and specifically on the "ift-Richtlinie NA-01/3 Allgemeiner Leitfaden zur Erstellung von Typ III Umweltproduktdeklarationen". ". (Guideline NA-01/3 - Guidance on preparing Type III Environmental Product Declarations) The publication and all its parts are protected by copyright. Any utilisation outside the confined limits of the consent of the publishers and is punishable. In particular, this applies to any form of reproduction, translations, storage on microfilm and the storage and processing in electronic systems.

Layout ift Rosenheim GmbH – 2021

Photographs (front page) SIEGENIA-AUBI KG

© ift Rosenheim, 2023



ift Rosenheim GmbH Theodor-Gietl-Str. 7-9 83026 Rosenheim Phone: +49 (0) 80 31/261-0 Telefax: +49 (0) 80 31/261-290 E-Mail: info@ift-rosenheim.de www.ift-rosenheim.de